




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : B65B 3/32, B67D 1/00, A23C 9/15	A1	(11) International Publication Number: WO 00/32475 (43) International Publication Date: 8 June 2000 (08.06.00)
(21) International Application Number: PCT/US99/27966 (22) International Filing Date: 24 November 1999 (24.11.99) (30) Priority Data: 09/204,676 3 December 1998 (03.12.98) US (71) Applicant (for all designated States except US): TETRA LAVAL HOLDINGS & FINANCE, SA [CH/CH]; 70, avenue Général-Guisan, CH-1009 Pully (CH). (72) Inventor; and (75) Inventor/Applicant (for US only): ANDERSSON, Sven-Arne [SE/US]; Apartment 301, 1261 Deerfield Parkway, Buffalo Grove, IL 60089 (US). (74) Agent: WEINSTEIN, Mitchell, J.; Welsh & Katz, Ltd., 22nd floor, 120 S. Riverside Plaza, Chicago, IL 60606 (US).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published With international search report.

(54) Title: PRODUCT VALVE COMPLEX FOR DUAL STREAM FILLING SYSTEM**(57) Abstract**

A product valve complex for a dual stream filling complex in which two different products are contained within two different chambers on a packaging machine and utilized to fill a container with both products simultaneously, or just one product. The product valve complex has a series of valves juxtaposed between two product supplies and the packaging machine. The valves may be controlled by a PLC for proper filling.



Best Available Copy

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

TITLE

PRODUCT VALVE COMPLEX FOR
DUAL STREAM FILLING SYSTEM

Corporate Docket Number TRX-0543

CROSS REFERENCES TO RELATED APPLICATIONS

This application is a continuation-in-part application of co-pending U.S. Patent Application Number 09/154,380, filed on September 16, 1998 which is a divisional application of U.S. Patent Number (Serial No. 08/897,554) filed on July 21, 1997 which is hereby incorporated by reference in its entirety.

STATEMENT REGARDING FEDERALLY SPONSORED
RESEARCH OR DEVELOPMENT

Not Applicable

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to product valves for filling machines. Specifically, the present invention relates to a product valves for a dual stream filling system for a filling machine.

Description of the Related Art

Packages formed from a blank are usually processed on a linear form, fill and seal packaging machine. Each blank is delivered to a mandrel of the packaging machine from a carton blank opener. The blank opener is fed with a series of blanks from a magazine. The magazine holds a stack of flat blanks that are erected on the carton blank opener prior to placement on the mandrel.

Once on the mandrel, each carton has its bottom formed prior to placement on a conveyor. On the conveyor, each carton may be fitted with a fitment and sterilized prior to filling and top sealing. Novel filling techniques as disclosed in U.S. Patent Number

5,687,779 have emerged to fulfill a need in the packaging industry, that need being the ability of a packaging machine to consecutively fill cartons with different products. This breakthrough in the packaging industry has created additional problems that must be met before the full potential of the novel filling systems is realized by dairies and other
5 producers of flowable food products such as milk, juice, yogurt and the like.

One of the most pressing needs is the ability to fill a single product on a dual stream filling system, especially the secondary product which may be metered at a much slower rate than the primary product. There is also a need to accomplish this single product filling without making major modifications to the dual stream filing system.

10

BRIEF SUMMARY OF THE INVENTION

One aspect of the present invention is a product filling system for filling a series of containers conveyed along a container path with a product. The product filling system includes product supplies, chambers, and a product valve complex. The first product supply is in flow communication with a first product supply line. The second product supply is in flow communication with a second product supply line. The primary chamber holds a primary product on a packaging machine. The primary chamber is in flow communication with a primary fill pipe. The secondary chamber holds a secondary product on the packaging machine. The secondary chamber is in flow communication with a secondary fill pipe, and the secondary fill pipe disposed within the primary fill pipe. The product valve complex has a first valve and a second valve juxtaposed between the first product supply line and a primary and secondary product outlets. The primary product outlet is in flow communication with the primary chamber and the secondary product outlet is in flow communication with the secondary chamber. The product valve complex also has a third valve and a fourth valve juxtaposed between the second product supply line and the primary and secondary product outlets.

Having briefly described this invention, the above and further objects, features and advantages thereof will be recognized by those skilled in the pertinent art from the following detailed description of the invention when taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

FIG. 1 is a isolated perspective view of a filling system of the present invention for a dual line packaging machine, the filling system having two dual chamber product tanks;

FIG. 2 is a top perspective view of a packaging machine having a filling system of the present invention;

FIG. 3 is a schematic diagram of a filling complex which utilizes the product valve complex of the present invention.

FIG. 3A is a schematic diagram of a filling complex for a double line machine which utilizes the product valve complex of the present invention.

FIG. 4 is a schematic diagram of a product system integrated with the product valve complex of the present invention.

FIG. 5 is a schematic diagram of the product valve complex of the present invention in one operational configuration.

FIG. 6 is a schematic diagram of the product valve complex of the present invention in an alternative operational configuration.

DETAILED DESCRIPTION OF THE INVENTION

An isolated view of a filling complex 20 is shown in FIG.1. The filling complex
5 is for a dual line packaging machine wherein two lines of cartons are processed to create
formed, filled and sealed cartons with a desired product. The filling complex has two
filling systems 22a-b positioned adjacent each other on a packaging machine. The most
prominent aspect of the two filling systems is the dual chamber product tanks 24a-b. The
product tanks 24a-b are disposed above the conveyor lines and near the top of the
10 packaging machine. A plurality of pumps are disposed beneath the tanks 26a-b and
further down the flow of product from the tanks 26a-b to the cartons are a pair of cleaning
boxes 28. The cleaning boxes 28 encompass a plurality of fill pipes, not shown in FIG. 1,
that will be described below.

There is illustrated in FIG. 2 a packaging system generally designated 30. The
15 packaging system 30 includes a packaging machine 32, a carton opener 34, a magazine
36. The packaging machine may be a typical linear form, fill and seal packaging
machine such as a TETRA REX® packaging machine available from Tetra Pak,
Incorporated of Chicago, Illinois. The packaging machine 32 may have a programmable
logic controller ("PLC") 38 to control the various operations of the packaging system 30.
20 Also, disposed within the packaging system 30 there may be a bar code reader 40 which
communicates via the PLC 38 the size and filling requirements of each carton to the
necessary components of the packaging machine 32, such as the filling complex 20. A
bar code reader for a packaging machine is disclosed in co-pending U.S. Patent
Application Number 09/_____ filed on April 21, 1998 and entitled Multi-Product
25 Packaging Machine With Bar Code Reader which is hereby incorporated by reference.

The packaging machine 32 for forming, filling and sealing cartons generally
includes a high hygiene zone 42 which is composed of a top sealing station 44 and the
filling complex 20, a sterilization station 48 which is composed of an ultraviolet radiation

station 50 and a hydrogen peroxide station 52, an optional fitment applicator station, and a bottom forming station 56. From an operational perspective, the front 60 of the packaging machine 32 is where the processing begins, and the rear 62 is where the finished cartons are dispensed for distribution.

- 5 The packaging machine 32 may be divided along a horizontal plane defined by a table top 64. The table top 64 divides the packaging machine 32 into an upper half 66 and a lower half 68. A frame 70 defines the general structure of the packaging machine 32 and supports the table top 64 and the various stations. The lower half 68 of the machine 32 includes servomotors, drive cylinders, cam drives and other components.
- 10 The upper half 66 includes the various stations, the product tanks 24a-b, the conveyor system 72, and other components to process cartons.

As shown in FIG. 3, each of the chambers 130, 132 have a level probe 150 disposed therein. The level probe measures the level of the product in a chamber and thereby controls the flow of product into the chamber 132. Air in the chambers 130, 132 is ventilated through outlets 106, 108 into through tubing 155 to the area about the plurality primary fill pipes 160 (and the cleaning box 28) in order to maintain like sterile air through the filling complex 20. The sterile air is supplied from a sterile air supply 170, not shown. Cleaning fluid, supplied from a cleaning fluid supply 171, not shown, may also be introduced to the chambers 130 and 132 through outlets 106 and 108.

- 20 In this embodiment, each of the plurality of primary fill pipes 160 has a secondary fill pipe 162 concentrically disposed therein. Such an arrangement is described in more detail in U.S. Patent Number 5,829,476. An alternative arrangement is described in U.S. Patent 5,687,779 which is hereby incorporated by reference. Additionally, those skilled in the art will recognize that the secondary fill pipes 162 may be outside of the primary
- 25 fill pipes 160 without departing from the scope and spirit of the present invention.

In operation, the primary chamber 130 is partially filled with a primary product such as skim milk. The secondary chamber 132 is partially filled with a secondary

product such as cream. Sterile air is introduced through outlets 106 and 108 to fill the chambers 130 and 132. As the product level changes, the sterile air is ventilated through the outlets 106 and 108 through tubing 155 and to the area about the fill pipes 160. The internal wall 134 maintains the separation of products, however, the internal wall 134
5 does allow for a transfer of heat from one chamber to another chamber. For example, if the secondary product is cream, the secondary chamber 132 is cooled by the primary chamber 130 which may contain skim milk. The flow of the primary product is usually greater than that of the secondary product allowing for cooler product from a main supply tank to cool the primary chamber 130. The lowered flow of the secondary product
10 allows for an accumulation of heat in the secondary chamber 132. The sharing of the internal wall 134 between chambers 130 and 132 allows for the transfer of heat thereby equalizing the temperatures of the chambers 130 and 132.

Returning to the filling operation, as cartons are conveyed below each primary fill pipe 160, the PLC will instruct the filling system 22 to fill the carton with a set amount of
15 each of the primary and secondary products to produce a desired product. For example, if two percent milk is desired, a small amount of cream will be dispensed into the carton followed, or concurrently with, a large amount of skim milk to produce the two percent product. FIG. 3A illustrates a dual stream filling complex 20 for a double line machine.

As shown in FIG. 4, the product system 200 includes a supply of a primary
20 product 202 and a supply of a secondary product 204. The product supplies 202 and 204 may be large vats that hold thousands of liters. Alternatively, the product supplies 202 and 204 may be tanker trucks that hold thousands of liters of product and are driven to the filling site for immediate deliver of the product thereby overcoming the need for large storage vats that require substantial space. The product supplies 202 and 204 are in flow
25 communication with the filling complex 20 on the packaging machine 32 through a series of pipes 208a-b. A product valve complex 210 is juxtaposed between the pipes 208a-b and the filling complex 20. The number of product supplies may be more than two

depending on the needs of the facility. A multiple of product supplies will all have piping 208 connected to the product valve mechanism for flow to the filling complex 20 of the packaging machine 32.

FIGS. 5 and 6 illustrate the product valve complex 210 in operation. The product valve complex 210 includes a plurality of valves 212a-d that control the flow of product to a plurality of outlets 214a-b which are in flow communication with the filling complex 20. The valves 212a-d are opened or closed depending on the flow of the products from the product supplies 202 and 204 to the chambers 130 and 132. The product valve complex 210 allows for the exchange of primary product and secondary product in the chambers. Thus, if the secondary product is the only product to be filled in a "product run", then the secondary product would be transferred to the primary chamber 130 of the product tank 24 since filling a single product on such a dual stream filling complex 20 may only be accomplished through the primary fill pipes 160.

Referring to FIGS. 3, 4 and 5, a primary product such as skim milk is dispensed from the primary product supply 202 through the pipe 208a to the product valve complex 210. A secondary product such as cream is dispensed from the secondary product supply 204 through the pipe 208b to the product valve complex 210. At the product valve complex 210, the valve 212a is closed and the valve 212b is open allowing for the flow of the skim milk into the secondary chamber 132 through outlet 214b and piping 216b. The secondary product, cream in this example, is allowed to flow into the primary chamber 130 since valve 212c is open and valve 212d is closed. The secondary product flows through outlet 214a through piping 216a and into the primary chamber 130. This allows for filling of a container through fill pipe 160 with only the secondary product, cream. Also, if the secondary product is the major product, and the primary product for a particular product run is the minor component, then the product valve complex 210 configuration of FIG. 5 may be utilized to obtain the necessary product.

The configuration of the product complex 210 in FIG. 6 is the opposite of FIG. 5 such that the primary product, skim milk, is allowed to flow into the primary chamber 130, and the secondary product is allowed to flow into the secondary chamber 132. FIG. 6 is the normal operation for dual stream filling through a dual stream filling complex.

- 5 Further, in FIG. 5, if the filling is only by a single product, the valves 212a and 212b may both be closed since the primary product would not be used for such a product run.

From the foregoing it is believed that those skilled in the pertinent art will recognize the meritorious advancement of this invention and will readily understand that while the present invention has been described in association with a preferred
10 embodiment thereof, and other embodiments illustrated in the accompanying drawings, numerous changes, modifications and substitutions of equivalents may be made therein without departing from the spirit and scope of this invention which is intended to be unlimited by the foregoing except as may appear in the following appended claims.
Therefore, the embodiments of the invention in which an exclusive property or privilege
15 is claimed are defined in the following appended claims.

CLAIMS

I claim as my invention:

- 5 1. A product filling system for filling a series of containers conveyed along a container path with a product, the product filling system comprising:
- a first product supply in flow communication with a first product supply line;
 - 10 a second product supply in flow communication with a second product supply line;
 - a primary chamber for holding a primary product on a packaging machine, the primary chamber in flow communication with a primary fill pipe;
 - a secondary chamber for holding a secondary product on the packaging machine, the secondary chamber in flow communication with a secondary fill pipe, the
 - 15 secondary fill pipe disposed within the primary fill pipe; and
 - a product valve complex having a first valve and a second valve juxtaposed between the first product supply line and a primary and secondary product outlets, the primary product outlet in flow communication with the primary chamber and the secondary product outlet in flow communication with the secondary chamber, the
 - 20 product valve complex also having a third valve and a fourth valve juxtaposed between the second product supply line and the primary and secondary product outlets.
2. The product filling system according to claim 1 wherein the container is a gable top carton.
- 25 3. The product filling system according to claim 1 wherein the container is a plastic bottle.

4. The product filling system according to claim 1 wherein the first, second, third and fourth valves are operable between a closed and an opened position, and the operability of the valves is controlled by a PLC.

5 5. A dual stream filling system comprising:

a first product supply in flow communication with a first product supply line;

a second product supply in flow communication with a second product supply line;

10 a primary chamber for holding a primary product on a packaging machine;

a secondary chamber for holding a secondary product on the packaging machine; and

a product valve complex having a plurality of valves juxtaposed between the first and second product supply lines and a primary and secondary product outlets in flow communication with the primary chamber and secondary chamber;

15 whereby the valves are operable between an opened and closed position thereby allowing for the flow of the primary product to one of the chambers and the secondary product to the other of the chambers.

20

1/6




FIG. 1

2/6




FIG. 2

3/6




FIG. 3

4/6




FIG. 3A

5/6




FIG. 4

6/6




FIG. 5




FIG. 6

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 99/27966

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 B65B3/32 B67D1/00 A23C9/15

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B65B B67D A23C F16K B67C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO 97 16344 A (TETRA LAVAL HOLDINGS & FINANCE ;ANDERSSON SVEN ARNE (US); OLUFSON) 9 May 1997 (1997-05-09) page 3, line 16 - line 22 page 5, line 3 - line 15; figures 1,3-5 ---	1,5
Y	DE 297 16 908 U (ELBE WERK ROSLAU GMBH) 2 January 1998 (1998-01-02) page 3, line 4 - line 27; figure 2 ---	1,5
A	US 3 938 537 A (CRULL WOLFGANG ET AL) 17 February 1976 (1976-02-17) column 4, line 1 - line 9; figure 1 ---	1,5
A	US 5 687 779 A (AXELSSON KARL-GUNNAR ET AL) 18 November 1997 (1997-11-18) cited in the application the whole document ---	1-5
	--- -/--	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

Z document member of the same patent family

Date of the actual completion of the international search

15 March 2000

Date of mailing of the international search report

22/03/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Béraud, F

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 232 023 A (ZIMMERLY ROBERT D) 3 August 1993 (1993-08-03) figure 1 -----	1, 5

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/US 99/27966

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
WO 9716344	A	09-05-1997	AU 7721696	A	22-05-1997
			BR 9611336	A	18-05-1999
			CA 2236100	A	09-05-1997
			EP 0865378	A	23-09-1998
			NO 981942	A	29-04-1998
DE 29716908	U	02-01-1998	NONE		
US 3938537	A	17-02-1976	DE 2220224	B	18-01-1973
			FR 2182101	A	07-12-1973
			GB 1433262	A	22-04-1976
US 5687779	A	18-11-1997	SE 500380	C	13-06-1994
			AU 680623	B	07-08-1997
			AU 4836993	A	12-04-1994
			CA 2144086	A	31-03-1994
			CZ 9500665	A	12-07-1995
			EP 0660671	A	05-07-1995
			FI 951232	A	16-03-1995
			HU 69617	A, B	28-09-1995
			JP 8501217	T	13-02-1996
			NO 951013	A	16-03-1995
			NZ 256148	A	25-06-1996
			PL 308117	A	24-07-1995
			RU 2093994	C	27-10-1997
			SE 9202689	A	18-03-1994
			WO 9406303	A	31-03-1994
			SK 31795	A	11-07-1995
			ZA 9306869	A	11-04-1994
			AU 689960	B	09-04-1998
			AU 3629395	A	19-04-1996
			BR 9509113	A	14-07-1998
			CA 2201290	A	04-04-1996
			DE 69511419	D	16-09-1999
			DE 69511419	T	20-01-2000
			EP 0781227	A	02-07-1997
			EP 0858947	A	19-08-1998
			EP 0864494	A	16-09-1998
			JP 10506865	T	07-07-1998
			NO 972649	A	26-06-1997
			NZ 293771	A	24-09-1998
			NZ 330709	A	28-01-1999
			WO 9609957	A	04-04-1996
US 5232023	A	03-08-1993	NONE		

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.